



## HOBO<sup>®</sup> UA-001-08 Data Logger

### 8K Pendant Temperature/Alarm (Waterproof) Data Logger

This value-priced data logger is both miniature and waterproof, making it a sensible monitoring solution for specific temperature monitoring applications. The HOBO Pendant<sup>®</sup> Temperature/Alarm Data Logger has one channel and is recommended for short-term shipping or long-term monitoring. This data logger features a visible LED light indicator, which warns users when preset parameters have been exceeded. This model stores 6.5K of 10-bit temperature readings. Use a solar radiation shield for accurate temperature measurement in sunlight applications. See RS1 Solar Radiation Shield (assembly required) and M-RSA (pre-assembled) Solar Radiation Shield.



#### Supported Measurements:

Temperature and Water Temperature

#### Key Advantages:

- Low-cost temperature with alarm indication or light intensity
- Waterproof housing for wet or underwater use
- Data readout in less than 30 seconds via fast Optic USB interface

## HOBO UA-001-08 Data Logger Specifications

**Measurement range:** -20° to 70°C (-4° to 158°F)

**Alarms:** High and low alarms can be configured for total amount of contiguous or non-contiguous time outside of user-defined limits between -20° and 70°C (-4° to 158°F)

**Accuracy:** ± 0.53°C from 0° to 50°C (± 0.95°F from 32° to 122°F), see Plot A

**Resolution:** Temperature: 0.14°C at 25°C (0.25°F at 77°F), see Plot A

**Drift:** Less than 0.1°C/year (0.2°F/year)

**Environmental Rating:** Top end: NEMA 6, IP67; Sensor end: IP68

### Response Time

**Airflow of 2 m/s (4.4 mph):** 10 minutes, typical to 90%

**Water:** 5 minutes, typical to 90%

**Time accuracy:** ± 1 minute per month at 25°C (77°F), see Plot B

### Operating Range

**In water/ice:** -20° to 50°C (-4° to 122°F)

**In air:** -20° to 70°C (-4° to 158°F)

**Water depth rating:** 30 m from -20° to 20°C (100 ft from -4° to 68°F), see Plot C

**NIST traceable certification:** Available for temperature only at additional charge; temperature range -20° to 70°C (-4° to 158°F)

**Battery life:** 1 year typical use

### Memory

**UA-001-08:** 8K bytes (approximately 6.5K sample and event readings)

**UA-001-64:** 64K bytes (approximately 52K sample and event readings)

**Materials:** Polypropylene case; stainless steel screws; Buna-N o-ring

**Weight:** 15.0 g (0.53 oz)

**Dimensions:** 5.8 x 3.3 x 2.3 (centimeters) and 2.3 x 1.3 x 0.9 (inches)

**Environmental Rating:** IP68

The CE Marking identifies this product as complying with the relevant directives in the European Union (EU).

## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

- ▶ Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation  
470 MacArthur Boulevard  
Bourne, MA 02532